


Repair & Rejacketing



CRSM Sleeves Heat-Shrink Wraparound Sleeve (1000 V)

CRSM sleeves close easily with a permanent locking system that consists of a raised rail profile and a stainless steel channel. These sleeves are made from crosslinked polyolefin, which equals or exceeds the material properties of the original cable jacket. CRSM sleeves fit a wide range of cable sizes and have unlimited shelf life.

- Qualified to ANSI C119.1
- Rated to ICEA electrical withstand test for 1000 volts
- RUS accepted for use as jacket restoration materials on JCN cable
- For use on standard poly- or elastomeric-insulated/jacketed cables or lead-jacketed cables, which may include aluminum or steel armoring.


Use as insulation for 1/C low-voltage power cable up to 1000 volts, and for jacket repair up to 35 kV or for general sealing applications. All CRSM sleeves are sealant-coated.

Selection Information: dimensions in inches (millimeters)

Primary Electrical Repair (1000 V)

Catalog Number	Sleeve Length	Cable and Jacket Repair Conductor Size Use Range (AWG/kcmil)	(Min.–Max.)	General Sealing Use Range (0–35 kV) (Min.–Max.)	Std. Pack
CRSM 34/10-200	8 (200)	#8-2/0	0.25-0.60 (6-15)	0.25-1.20 (6-30)	3
CRSM 34/10-1200	48 (1219)	#8-2/0	0.25-0.60 (6-15)	0.25-1.20 (6-30)	5
CRSM 53/13-200	8 (200)	3/0-400	0.60-0.95 (15-24)	0.60-1.80 (15-46)	10
CRSM 53/13-1200	48 (1219)	3/0-400	0.60-0.95 (15-24)	0.60-1.80 (15-46)	5
CRSM 84/20-750	30 (750)	500-1000	0.95-1.40 (24-36)	0.95-2.70 (24-69)	10
CRSM 84/20-1200	48 (1219)	500-1000	0.95-1.40 (24-36)	0.95-2.70 (24-69)	5
CRSM 107/29-1000	40 (1000)	1000-2000	1.30-2.00 (33-51)	1.30-3.60 (33-91)	10
CRSM 107/29-1200	48 (1219)	1000-2000	1.30-2.00 (33-51)	1.30-3.60 (33-91)	5
CRSM 143/36-1200	48 (1219)			1.65-4.95 (42-126)	5
CRSM 198/55-1200	48 (1219)			2.50-6.50 (64-165)	5

Damage	Total Seal Length
<3 (<76)	3 (76)
3-12 (76-305)	4 (102)
12-24 (305-610)	6 (152)
>24 (>610)	8 (203)



Cut Sleeve Length = Damage Length + Total Seal Length

Ordering Information

1. Select the appropriate catalog number for either primary electrical repair (1000 volts max.) or general sealing applications. Electrical repair selections are based on typical dimensions for low voltage insulated cable. Confirm selection with cable dimensions to assure proper sizing.
2. Use the "Primary electrical repair" columns for electrical repair applications (when CRSM is in direct contact with the conductor).
3. Use the "General sealing and jacket repair use range" column for general rejacketing or sealing applications (when CRSM is not in direct contact with the conductor).
4. Package does not contain connectors.
5. Kits include a wraparound sleeve and stainless steel channel closure. Both can be field-cut for shorter requirements.
6. Related test report: [EDR-5124](#), [EDR-5192](#).
7. UV resistant test report: [EDR-5361](#).
8. CRSM 34/20 are available in shorter standard lengths by ordering the corresponding CRSM-CT kits. (The use ranges in the selection information table still apply).